

DECLARATION OF PERFORMANCE

Manufacturer	KORAMIC YAPI KİMYASALLARI SANAYİ TİCARET ANONİM ŞİRKETİ	
Contact Information	Bozüyük OSB 10. Cadde No: 7 Bozüyük, Bilecik – Turkey info@koramic.com.tr	
Registered Trademarks	VITRAFİX EPOXY	
Unique Product Identification Codes	F22401005	
Intended Use	It is used for joint applications among ceramics in horizontal and vertical surfaces in interior and exterior places. Thanks to its feature of watertight and non-dunting, it is suitable to be used in wet areas, pools, terraces and broad areas. It is ideal to be used in the areas requiring high resistance to acid and bases and high mechanical strength	
Related Directive	305/2011/EU Construction Materials Regulations	
Harmonized Standard	TS EN 13888 / March 2010	
System of Constancy of Performance	System 4	
Declaration of Performance		
Essential Characteristics	Performance	Harmonised Technical Specification
Abrasion resistance	$\leq 250 \text{ mm}^3$	TS EN 13888 / Mart 2010
Flexural strength after dry storage	$\geq 30 \text{ N/mm}^2$	TS EN 13888 / Mart 2010
Compressive strength after dry storage	$\geq 45 \text{ N/mm}^2$	TS EN 13888 / Mart 2010
Shrinkage	$\leq 1,5 \text{ mm/m}$	TS EN 13888 / Mart 2010
Water absorption after 240 min	$\leq 0,1 \text{ g}$	TS EN 13888 / Mart 2010

We hereby declare and engage that; the stated product and models are produced as covering the requirements of the related directives and harmonized standards and in conformity with the declared performance. We performed the obligations under System 4 and issued this declaration of conformity. This declaration and performance do not provide guarantee right about the product and its features and the conformity, which is under sole responsibility of the manufacturer, is valid as long as terms of use are followed.

2021-CG-04
12.03.2021



Feyza BODUR
AR-GE, Üretim, Kalite Kontrol
ve
KYS Direktörü